Safety Data Sheet

Methanol

Version: V1.0.0.1

Creation Date : 2016/06/13 Revision Date : 2016/06/13



*Prepared according to Canadian Hazardous Products Regulations

Identification of the chemical and supplier

Product identifier

Product Name	Methanol
Cat No.	20160613-3
Synonyms	Wood alcohol, wood spirit and methyl alcohol
CAS No.	67-56-1
EC No.	200-659-6
Molecular Formula	CH₄O

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Laboratory chemicals, industrial and pharmaceutical solvent and raw material.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company		
Address of the company		
Post code		
Telephone number		
Fax number		
E-mail address		

Emergency phone number

Emergency phone number

2 Hazards identification

Hazard classification according to GHS

Flammable Liquids	Category 2
Acute Toxicity - Oral	Category 3
Acute Toxicity - Dermal	Category 3
Acute Toxicity – Inhalation	Category 3
Specific Target Organ Toxicity (Single Exposure)	Category 1

Label elements

Hazard pictograms	
Signal word	Danger
Hazard statements	
H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs

| Precautionary statements

Prevention

Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P233	Keep container tightly closed.	
P240	Ground and bond container and receiving equipment.	
P242	Use non-sparking tools.	
P243	Take action to prevent static discharges.	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P264	Wash thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves/protective clothing/eye protection/face protection	
Response		
P312	Call a POISON CENTER/doctor, if you feel unwell.	
P330	Rinse mouth.	
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	

P312	Call a POISON CENTER/doctor, if you feel unwell.
P330	Rinse mouth.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

Disposal

P501	Dispose of contents/container international regulations.	in accordance	with	local/regional/national/
141 180000 141	international regulations.			

Other hazards

Not applicable

| Hazard description

Physical and chemical hazards

Highly flammable liquids, its vapor and air mixture can form explosive mixture.

Health hazards

Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the product during the course of normal handling, may produce toxic effects. There is strong evidence to suggest that this material can cause, if inhaled once, serious, irreversible damage of organs. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
Ingestion	Strong evidence exists that exposure to the material may produce serious irreversible damage (other than carcinogenesis, mutagenesis and teratogenesis) following a single exposure by swallowing. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. Methanol may produce a burning or painful sensation in the mouth, throat, chest, and stomach. This may be accompanied by nausea, vomiting, headache, dizziness, shortness of breath, weakness, fatigue, leg cramps, restlessness, confusion, drunken behaviour, visual disturbance, drowsiness, coma and death.
Skin Contact	Toxic in contact with skin, systemic effects may result following absorption. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.
Eye	This product may cause temporary discomfort following direct contact with the eye.

Environmental hazards

Please refer to 12th chapter of SDS.

Composition/information on ingredients

Component	Cas No.	EC No.	Concentration (weight percent, %)
Methanol	67-56-1	200-659-6	99.0

4 First aid measures

Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to
	the doctor in attendance.
Evo contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a
Eye contact	physician if fell uncomfortable.
	Take off contaminated clothing and shoes immediately. Wash off with plenty of
Skin contact	water for at least 15 minutes and consult a physician if fell uncomfortable.
	Do not induce vomiting. Never give anything by mouth to an unconscious
Ingestion	person. Call a physician or Poison Control Center immediately.
	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use
Inhalation	
	breathing, give artificial respiration and consult a physician immediately.

Protecting	of	first-	ide	a re
Protecting	OI	III St-c	alue	2113

Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

Firefighting measures

Extinguishing media

Suitable	extinguishing
	media
Unsuitable	extinguishing
	media

Dry chemical, carbon dioxide or alcohol-resistant foam.

Do not use a solid water stream as it may scatter or spread fire.

Specific hazards arising from the substance or mixture

- 1 Will form explosive mixtures with air.
- Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/ or vapour concentration.
- 3 Vapours may travel to source of ignition and flash back.
- 4 Liquid and vapour are flammable.
- 5 May emit poisonous fumes on fire.
- 6 Containers may explode when heated.
- 7 Fire exposed containers may vent contents through pressure relief valves.
- 8 May expansion or decompose explosively when heated or involved in fire.

Advice for firefighters

- As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

- 1 Avoid breathing vapors and contacting with skin and eye.
- 2 Beware of vapours accumulating to form explosive concentrations.
- 3 Vapours can accumulate in low areas.
- Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
- 5 Ensure adequate ventilation. Remove all sources of ignition.
- 6 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
- 7 Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.

Environmental precautions

1 Prevent further leakage or spillage if safe to do so.

2 Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

- Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
- 3 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7 Handling and storage

Precautions for handling

- 1 Avoid inhalation of vapors.
- 2 Use only non-sparking tools.
- To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
- 4 Use explosion proof equipment.
- 5 Handling is performed in a well ventilated place.
- 6 Wear suitable protective equipment.
- 7 Avoid contact with skin and eyes.
- 8 Keep away from heat/sparks/open flames/ hot surfaces.
- 9 Take precautionary measures against static discharges.

Precautions for storage

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/ hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

8 Exposure controls/personal protection

Control parameters

Occupational Exposure limit values

Component		Limit value - Eight hours		Limit value - Short term	
	Country/Region	ppm	mg/m³	ppm	mg/m³
	USA - OSHA	200	260	9/222	ð <u>122</u> 0
	South Korea	200	260	250	310
Methanol	Ireland	200	260	50 55	0.5578
67-56-1	Germany (AGS)	200	270	800	1080
	Denmark	200	260	400	520
	Australia	200	262	250	328

Biological limit values

175 F 1 1 1	I bear by	Karana Sana Carana and Arana and Ara	
Riological	limit values	No information available	
Diviouical	IIIIIL VAIUES I		

Monitoring methods

- EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
- 2 GBZ/T 160.1~GBZ/T 160.81-2004 Determination of toxic substances in workplace air (Series standard).

Engineering controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

Personal protection equipment

Fye protection Hand protection Respiratory protection Respiratory protection Kespiratory protection Respiratory protection Respiratory protection Wear fire/flame resistant/retardant clothing and antistatic boots. Wear fire/flame resistant/retardant clothing and antistatic boots.

9 Physical and chemical properties

Physical and chemical properties

Appearance Colorless transparent liquid Odor Alcohol-like Odor threshold No information available pH 7 Melting point/freezing -98		
Odor threshold No information available pH 7 Melting point/freezing98		
pH 7 Melting point/freezing -98	Alcohol-like	
Melting point/freezing _qg	No information available	
point(°C)		
Initial boiling point and boiling range(°C)		
Flash point(Closed cup,°C) 12		
Evaporation rate 1.9~2.1 (n-butyl acetate=1.0)	1.9~2.1 (n-butyl acetate=1.0)	
Flammability(solid, gas) Not applicable		
Upper/lower explosive Upper limit: 36-44; Lower limit: 5.5-6		
Vapor pressure(kPa) 12.3		
Vapor density(Air = 1) 1.11		
Relative density(Water=1) 0.791		
Solubility(mg/L) Miscible with water		
n-octanol/water partition coefficient -0.82~-0.66		
Auto-ignition 455-464		

temperature(°C)	
Decomposition temperature(°C)	No information available
Viscosity	0.597 mPa.s(20℃)

10 Stability and reactivity

Stability and reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.		
Chemical stability	Stable under proper operation and storage conditions.		
No. of the control of	In contact with oxidants causes severe reactions, and may cause a fire or explosion.		
Conditions to avoid	Incompatible materials, heat, flame and spark.		
Incompatible materials	Oxidants, alkali metals, alkaline earth metals and aluminum.		
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.		

111 Toxicological information

Acute toxicity

Component	Cas No.	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Methanol	67-56-1	5628mg/kg(Rat)	15800mg/kg(Rabbit)	83.867mg/L(Rat)

Carcinogenicity

ID	Cas No.	Component	IARC	NTP
1	67-56-1	Methanol	Not Listed	Not Listed

Others

Methanol(Component)			
Skin corrosion/irritation	Drying-out effect resulting in rough and chapped skin.		
Serious eye damage/irritation	Irritation of mucous membranes.		
Skin sensitization	Based on available data, the classification criteria are not met.		
Respiratory sensitization	on Based on available data, the classification criteria are not met.		
Reproductive toxicity	Based on available data, the classification criteria are not met.		
STOT-single exposure	Causes damage to organs(Category 1)		
STOT-repeated exposure Based on available data, the classification criteria are not met.			
Aspiration hazard	Aspiration hazard Based on available data, the classification criteria are not met.		
Germ cell mutagenicity	ty Genotoxicity in vitro- Ames test result: negative.		
Reproductive toxicity(additional)	Based on available data, the classification criteria are not met.		

12 Ecological information

| Acute aquatic toxicity

Component	Cas No.	Fish	Crustaceans	Algae
Methanol 67-56-1	C7 EC 1	LC ₅₀ : 24000mg/L	EC ₅₀ : 24500mg/L	No information
	(96h)(Fish)	(48h)	available	

Chronic aquatic toxicity

Chronic aquatic toxicity No information available

Others	
Persistence and	Readily biodegradable (OECD Test Guideline 301D , 30 d , 99%); Biochemical
degradability	Oxygen Demand (BOD) 600~1120 mg/g (5d) .
Bioaccumulative potential	Lin actional/water partition coefficient : (1 / // bloaccumulation is not expected
Mobility in soil	No information available.
	Methanol does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

13 Disposal considerations

Disposal considerations

Waste chemicals	If medical advice is needed, have product container or label at hand.			
	Containers may still present chemical hazard when empty. Keep away from and ignition source of fire. Return to supplier for recycling if possible.			
Disposal recommendations	Refer to section 13.1and 13.2.			

14 Transport information

Label







IMDG-CODE

UN number	1230
UN proper shipping name	METHANOL
Transport hazard class	
Transport subsidiary hazard class	6.1
Packing group	
Special provisions	279
Limited quantities	1L
Excepted quantities	E2
Marine pollutant (Yes or no)	No
EmS No.	F-E,S-D

ICAO/IATA-DG

UN number	1230
UN proper shipping name	METHANOL
Transport hazard class	
Transport subsidiary hazard class	6.1
Packing group	
Excepted quantities	E2
Passenger and Cargo Aircraft Limited Quantity Packing Instructions	Y341
Passenger and Cargo Aircraft Limited Quantity Maxium net Quantity per Package	1 L
Passenger and Cargo Aircraft Packing Instructions	352
Passenger and Cargo Aircraft Maxium net Quantity per Package	1 L
Cargo Aircraft Packing Instructions	364
Cargo Aircraft Maxium net Quantity per Package	60 L
Special provisions	A104、A113
ERG code	3P

UN-ADR

OCCUPATION WHITTEN SOUTHWEST	
UN number	1230
UN proper shipping name	METHANOL
Transport hazard class	
Transport subsidiary hazard class	6.1
Packing group	
Special provisions	279
Limited quantities	1L
Excepted quantities	E2

15 Regulatory information

International chemical inventory

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECI	AICS
Methanol	Listed							

[EINECS] European Inventory of Existing Commercial Chemical Substances

【TSCA】 United States Toxic Substances Control Act Inventory

[DSL] Canadian Domestic Substances List

[IECSC] China Inventory of Existing Chemical Substances

[NZIoC] New Zealand Inventory of Chemicals

[PICCS] Philippines Inventory of Chemicals and Chemical Substances

[KECI] Existing and Evaluated Chemical Substances[AICS] Australia Inventory of Chemical Substances

16 Others

Information on revision

Creation Date	2016/06/13	
Revision Date	2016/06/13	
Reason for revision		

Reference

[1]IPCS:The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.

[2]IARC, website: http://www.iarc.fr/.

[3]OECD: The Global Portal to Information on Chemical Substances, website:

http://www.echemportal.org/echemportal/index?pageID=0&request locale=en.

[4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.

[5] NLM: Chem IDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.

[6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.

[7]U.S. Department of Transportation:ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.

[8]Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

Abbreviations and acronyms

CAS - Chemical Abstracts Service CMR - Carcinogens, mutagens or substances toxic to reproduction

PC-STEL- Short term exposure limit PC-TWA - Time Weighted Average

DNEL - Derived No Effect Level IARC - International Agency for Research on Cancer

RPE - Respiratory Protective Equipment PNEC - Predicted No Effect Concentration

LC₅₀ - Lethal Concentration 50% LD₅₀ - Lethal Dose 50%

NOEC -No Observed Effect Concentration EC₅₀ - Effective Concentration 50%

PBT - Persistent, Bioaccumulative, Toxic POW - Partition coefficient Octanol:Water

BCF - Bioconcentration factor (BCF) vPvB - very Persistent, very Bioaccumulative

IMDG-International Maritime Dangerous Goods ICAO/IATA-International Civil Aviation Organization/International Air

Transportation Association

UN-The United Nations ACGIH-American Conference of Governmental Industrial Hygienists

NFPA-National Fire Protection Association

OECD-Organization for Economic Co-operation and Development

Disclaimer

This Safety Data Sheet (SDS) was prepared according to Canadian Hazardous Products Regulations. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this

document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.